

BACK LINE REQUIREMENTS

(Substitutions of equal quality OK, please confirm with the the band in advance.)

Lead Vocal

Professional quality Shure Wireless Microphone for the lead singer

Guitar1:

(1) Marshall JCM 2000 TSL-100 100 watt 3 Channel amp head with footswitch and 2 4x12 Marshall Cabinets.

Guitar2:

(1) Marshall JCM 2000 TSL-100 100 watt 3 Channel amp head with footswitch and 2 4x12 Marshall Cabinets.

Bass:

(1) AMPEG SVT CLASSIC ALL TUBE 300 WATT HEAD and AMPEG SVT 8X10 EXTENSION CABINET

Drums:

Pearl, DW, Yamaha (pro "quality" kit)

22" Kick drum 8, 10 or 12" Rack toms, 2 preferred 14, 16 or 18" Floor toms, 2 preferred 14" snare drum

- 1 DOUBLE Kick drum pedal
- 1 Throne
- 1 Hi hat stand
- 4 boom cymbal stands

Sabian, Paiste or Zildjian cymbals (pro "quality" kit) 20 or 21" Ride 1 - 16" crash 1 - 17" or 18" crash

1 - 16" or 18" China cymbal

STAGE PLOT

Input List

Nickelblack uses 4 monitor mixes

Lead Vocal Monitor Mix: Vocals, Guitars, Bass, PC, Acoustic Guitar, Kick and Snare and OHs in some situations.

Lead Guitar Monitor Mix: Vocals, Guitars, Bass, PC, Acoustic Guitar, Kick and Snare in some situations.

Bass Monitor Mix: Vocals, Guitars, Bass, PC, Acoustic Guitar, Kick and Snare in some situations.

Drums Monitor Mix: Vocals, Guitars, Bass, PC, Acoustic Guitar, Kick and Snare in some situations.

Microphone & Monitor Requirements

Total of 4 Monitors, 1 monitor for each band member.

- **1** Wireless professional Shure SM58 Microphone with received for lead singer.
- 2 Shure SM58 Microphones with cables for drum and guitar player.
- **1 Shure Super 55 Microphones plus Radio FX from mixer.**

One direct box to be placed at Drum set.

One direct box to be placed near Guitar Stage Left.

4 Microphone stands with boom.

All cables needed for Microphones, Direct Box and monitors.

Drums: Standard Drum Microphones.

We will need 4 monitor mixes.